



## Features

- For shallow recessed channels
- Made of lightweight double anodized aluminum
- Frosted lens protects light source while evenly diffusing light
- Field cuttable extrusion and lens
- Aluminum provides excellent heat dissipation
- Optional end caps and mounting clips available
- Compatible with most Trulux Tape Light

## Available Lengths

39-3/8" (1 meter)

## Available Finishes



Anodized Aluminum

## Compatible Tape Light

- Trulux Single Color
- Trulux Tunable CCT (excludes Double Row)
- Trulux RGB

## TRULUX™ Mini Double Flange Extrusion

Similar to the Mini, the Double Flange only needs a channel of only 1/4" depth. The Mini Double Flange is a recess mount only extrusion. It can be altered for IP65 use in wet locations. Use the frosted UV resistant/flame retardant lens, made of high quality polycarbonate material. Propylene caps finish the ends.

### Best suited applications:

Stairs, handrails, display shelving and cases, niche and accent lighting

## Ordering Information

<b>PE-AA1DF-1M*</b>	Mini Double Flange Aluminum Extrusion
<b>PE-UVLENS-1M</b>	Frosted Polycarbonate UV Lens
<b>PE-AA1DF-END*</b>	Mini Double Flange End Cap

\*Mini Double Flange Extrusion is available as special order only. Please allow up to 2 weeks for order processing.

